

Model
Category

Dingli JCPT2223DC

4WD Rough Terrain Scissor Lift

Working Height

22.0m

Stowed Height

3.86m

Width

2.46m

Lifting Capacity

750kg

Weight

13,000kg

Power

Battery



STANDARD FEATURES

- Proportional Controls
- Self-lock Gate On Platform
- 4WD
- 4WS
- Self-leveling hydraulic outriggers
- Automatic brake system
- Cylinder holding valve
- Onboard diagnostic system
- Tilt sensor with alarm
- All motion alarm
- Horn
- Hour meter
- Safety brackets
- Folding guardrails
- Flashing beacon
- Slide-out engine tray
- Emergency stop button
- Anti-restart engine protection
- European III emission engine
- Hydraulic oil cooler
- Vertical lift maintenance
- Automatic single roll out deck
- Oscillating Chassis
- Axle Drive

IPAF Category **3a**

Do you hold a valid operator's licence?

The Powered Access Licence (PAL) Card is recognised worldwide as proof of platform operator training to the highest standard.

It is issued by the International Powered Access Federation (IPAF) to platform operators who successfully complete a training course at an IPAF approved training centre.

Quick checklist for employers and operators using powered access machines:

- ✓ **I have an IPAF PAL card**
- ✓ **Date is still valid (Licence expires after 5 years)**
- ✓ **All categories for the machine's being used are listed on the PAL card (e.g. 3a, 3b, PAV).**

If you can answer yes to all three, you're good to go!

If not, please call us to discuss your requirements and arrange a training course.



Dingli JCPT2223DC 4WD Rough Terrain Scissor Lift

Dimensions	JCPT2223DC
Work Height	22.00m
Platform Height	20.00m
Overall Width	2.46m
Overall Length	4.95m
Stowed Height (Rails Up)	3.86 m
Stowed Height (Rails Down)	3.00m
Platform Size(Length × Width)	4.59 × 2.25m
Platform Extension Size	2.70m
Star Group Code	SE6697
Specifications	JCPT2223DC
Ground Clearance(Raised/Stowed)	0.40m
Wheelbase	3.30m
Turning Radius(Inside/Outside)	1.25m/3.40m
Weight	13400kg
Gradeability	30%
Max. Working Slope	2°/3°
Lift Time (With Rated Load)	25 sec
Up/Down Speed	90/100sec
Drive Speed (Stowed)	5.0km/h
Drive Speed (Raised)	0.4km/h
Maximum Drive Height	Full Height
Lifting Capacity	750kg
Distributed Capacity (Extension Deck)	750kg
Battery	48V/630Ah
Charger	48V/60A
Maximum Persons (Indoor/Outdoor)	4
Tyre Type	Solid, N/M
Tyre Size	36 × 14-20



Watch the Dingli JCPT2223DC in action



TRAINING

SALES

HIRE

0844 682 0000



NATIONAL
COVERAGE

ACCESS
ALLIANCE

We offer a true UK wide hire service via a network of strong regional access companies who share Star Platforms' values, offering high service levels and quality equipment.

For more information head to our website starplatforms.co.uk

This brochure is for illustrative purpose only and based on the latest information at the time of printing. CE marked work platforms are in conformance to Machinery Directive 2006/42/EC. E&OE