



Genie Z-45/25 RT & Z-45/25J RT

Diesel Articulating Booms

STANDARD FEATURES

- Self-levelling platform
- Hydraulic platform rotation
- Proportional joystick controls
- Thumb rocker steering
- Drive enable
- AC power cord to platform
- Horn
- Hour meter
- Tilt alarm
- Descent & travel alarms
- Flashing beacon
- 355° non-continuous turntable rotation
- Positive traction drive
- Two speed wheel motors
- 12 V DC auxiliary power
- Engine protection package
- Deutz intake air heater
- Swing out engine tray

IPAF Category 3b

Do you hold a valid operator's licence?

The PAL Card (Powered Access Licence) is recognised worldwide as proof of platform operator training to the highest standard.

It is issued by the International Powered Access Federation (IPAF) to platform operators who successfully complete a training course at an IPAF approved training centre.

Quick checklist for employers and operators using powered access machines:

- ✓ I have an IPAF PAL card.
- ✓ Date is still valid (Licence expires after 5 years).
- ✓ All categories for the machine's being used are listed on the PAL card (e.g. 3a, 3b, PAV).

If you can answer yes to all three, you're good to go!

If not, please call us to discuss your requirements and arrange a training course.



Z-45/25 RT & Z-45/25J RT


Diesel Articulating Booms

Specifications	Z-45/25 RT	Z-45/25J RT
Working height maximum	15.97 m	16.05 m
Platform height maximum	13.97 m	14.05 m
Horizontal reach maximum	7.49 m	7.52 m
Up and over clearance maximum	7.14 m	7.14 m
A Platform length	0.76 m	0.76 m
B Platform width	1.83 m	1.83 m
C Height - stowed	2.13 m	2.13 m
D Length - stowed	5.38 m	6.65 m
E Width	2.29 m	2.29 m
F Wheelbase	2.03 m	2.03 m
G Ground clearance - centre	0.37 m	0.37 m


Productivity	Z-45/25 RT	Z-45/25J RT
Lift capacity	227 kg	227 kg
Platform rotation	180°	160°
Vertical Jib rotation	n/a	135°
Turntable rotation	355° non-continuous	
Turntable tailswing	zero	zero
Drive speed - stowed	7.24 km/h	7.24 km/h
Drive speed - raised	1.00 km/h	1.00 km/h
Gradeability - 4WD - stowed	45%	45%
Turning radius - inside	1.68 m	1.68 m
Turning radius - outside	4.50 m	4.50 m
Controls	12 V DC proportional	
Tyres	355/55 D20	355/55 D20

Power	Z-45/25 RT	Z-45/25J RT
Auxiliary power unit	12 V DC	12 V DC
Hydraulic tank capacity	83 L	83 L 22
Fuel tank capacity	64.4 L	64.4 L


Weight	Z-45/25 RT	Z-45/25J RT
CE 4WD (air tyres)	6,078 kg	6,123 kg
CE 4WD (foam filled tyres)	6,415 kg	6,460 kg



Range Of Motion Z-45/25



Range Of Motion Z-45/25J



Hire • Sales • Training

0844 682 0000

www.starplatforms.co.uk

info@starplatforms.co.uk

UK Coverage

We offer a true UK wide hire service via a network of strong, regional access companies who share Star Platforms' values, offering high service levels and quality equipment.

